




FI-CS6D

Two-way ceiling speaker with Dante audio network



The ceiling speaker FI-CS6D is white, with an Metal housing and metal protecting grille.

The simple and discreet design and good reproduction of both speech and music enable it to fit perfectly into any architectural environment. The built-in Dante enables it to be connected to constant voltage lines with variable power.

The FI-CS6D is a ceiling speaker with separate woofer and tweeter. It provides high sound quality in your installation.

This ceiling speaker is designed to offer professional solution to contractors.

Product Features

- Build-in Dante audio network protocol module
- Single-stage power conversion(DC-AC)
- Soft switching technology
- Bidirectional energy recovery technology
- Precise PSM(Phase Modulation) technology
- Two-way ceiling speaker for commercial audio applications
- Separate woofer and tweeter for excellent sound quality
- Full protection of the transformer
- Convenient magnetic front Grill
- Easy, fast and safe fastening system
- High resistant Metal housing that protects it from heat and ensure long lifetime
- Suitable for paging and background music applications

Products Applications

- The ceiling speaker is ideal for applications where excellent sound quality is needed for medium-volume music playback and paging, such as in music cafes, retail stores, airports, reception / waiting rooms, lounges, courtrooms, convention centers, hotels, educational facilities and more.



Product Specification

General Specification	
Type	FI-CS6D
Frequency Response	120Hz-20Khz
Sensitivity	89 dB @ 1 watt / 1 meter
Maximum SPL (1W/1M)	116dB
Rated power	60W @ 8Ω
coverage angle	110°
Input interface	RJ-45
Audio transmission protocol	Dante
Audio routing control	Dante Controller
Power input	802.3af/802.3at/802.3bt compatible
Heat dissipation	natural convection cooling
Hole for mounting(mm)	Φ: 270 / Depth: 176
Dimensions(mm)	Φ: 316 / Depth: 197
Physical Specification	
Material (panel)	Metal
Grille	Powder Coated Iron Mesh
Component (L.Speaker)	6" (PCK + PF) Woofer
Component (H.Speaker)	3/4" Silk
Finished Colour	White RAL 9016
Unit Weight	5.3 Kg
Gross Weight	12 Kg / 2 pcs
Packing Dimension	75 x 38 x 28.5 cm

